

**AMINOL**

Aminol Special Generation SLD5 15W-40 CK-4

Product Data Sheet

Engine oil

Product description

Aminol Special Generation SLD5 15W-40 CK-4 is a top-notch diesel engine oil made with high-quality base stocks and a carefully balanced additive package. It's designed to work seamlessly with exhaust aftertreatment systems, such as diesel particulate filters (DPFs), diesel oxidation catalysts (DOCs), and selective catalytic reduction (SCR).

Application

Aminol Special Generation SLD5 15W-40 CK-4 can be used in naturally aspirated and turbocharged heavy-duty diesel engines, both in mobile and stationary equipment, where the API CK-4 service category and SAE 15W-40 viscosity grade are specified.

Features & Benefits

- Exceptional soot dispersancy and wear control
- Improved thermal stability and oxidation resistance
- Prolonged life of exhaust aftertreatment systems
- Effective protection of engine parts from all types of corrosion
- Reduced foaming and efficient resistance to aeration
- Excellent viscosity-temperature behavior
- Seal-friendly formulation

Typical Properties

Property	Unit	Test method	Typical value
Kinematic Viscosity at 100°C	cst	ASTM D 445	14.50
Kinematic Viscosity at 40°C	cst	ASTM D 445	100.1
Viscosity Index	-	ASTM D 2270	150
Flash Point, COC	°C	ASTM D 92	234
Pour Point	°C	ASTM D 7346	-27
TBN	mg KOH/g	ASTM D 2896	9.2
Sulphated Ash Content	%	ASTM D 874	0.98
Density at 15°C	g/ml	ASTM D 4052	0.872

Typical property characteristics are based on current production. Whilst future production will conform to Aminol specifications, variations in these characteristics may occur.

Performance claims

- API CK-4/SN
- ACEA E9

**AMINOL**

Aminol Special Generation SLD5 15W-40 CK-4 Product Data Sheet

Engine oil

- MB-228.31
- MAN M3775
- Volvo VDS-4.5
- Mack EOS-4.5
- Renault Trucks RLD-4
- Cummins CES 20086
- Caterpillar ECF-3
- Detroit Diesel DDC 93K222
- Deutz DQC III-18LA

ALCO LLC recommends this product for vehicles with the following specifications:

- MB 228.3
- Ford WSS-M2C171-F1
- MTU Type 2.1
- Deutz DQC III-10 LA
- JASO DH-2
- IVECO: T2 E7

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained. For further guidance on Product Health & Safety, refer to the appropriate Safety Data Sheet, which can be obtained upon request or through our website: www.aminol.az

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil, or water.

Available pack sizes

- | | |
|------------------------|--------------------------|
| • 1 L Canister plastic | • 20 L Canister plastic |
| • 4 L Canister plastic | • 30 L Canister plastic |
| • 5 L Canister plastic | • 60 L Canister plastic |
| • 6 L Canister plastic | • 200 L Drum sheet metal |
| • 7 L Canister plastic | • 1000 L Container |

Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.

**AMINOL**

Aminol Special Generation SLD5 15W-40 CK-4 Product Data Sheet

Engine oil

-
- Products should not be stored above 60 °C, exposed to hot sun, or freezing conditions.

Notes

This data sheet and the information it contains are believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application, and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services, and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.