

Product Data Sheet

Tomoil™ Motobike 4T 10W-40

Motorcycle oil

Product description

Tomoil™ Motobike 4T 10W-40 represents a cutting-edge 4-stroke motorcycle oil crafted to guarantee top-notch engine performance and protection, even in the most demanding circumstances. It incorporates high-quality base stocks and performance-boosting additives, resulting in superior lubrication, optimal engine cleanliness, effective friction management, and reduced wear.

Application

Tomoil™ Motobike 4T 10W-40 is suitable for high-performance, air, and water-cooled four-stroke motorcycles, whether equipped with or without a wet clutch. It is also ideal for motorcycles with exhaust after-treatment systems such as catalytic converters or secondary air injection

Features & Benefits

- Protects against wear, deposits, and sludge
- Extends engine life and improves performance
- Maintains cleanliness and reduces oil consumption
- Ensures superior performance in varied temperatures

Typical Properties

Property	Unit	Test method	Typical value
Kinematic Viscosity at 100°C	cst	ASTM D 445	14.50
Kinematic Viscosity at 40°C	cst	ASTM D 445	103.4
Viscosity Index	-	ASTM D 2270	145
Flash Point, COC	°C	ASTM D 92	224
Pour Point	°C	ASTM D 7346	-30
TBN	mgKOH/g	ASTM D2896	7.7
Density at 15°C	g/ml	ASTM D 4052	0.872

Typical property characteristics are based on current production. Whilst future production will conform to Tomoil™ specifications, variations in these characteristics may occur.

Performance claims

- API SN
- JASO MA2

Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website: www.tomoil.de

- **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Available pack sizes

- | | |
|------------------------|--------------------------|
| • 1 L Canister plastic | • 20 L Canister plastic |
| • 4 L Canister plastic | • 30 L Canister plastic |
| • 5 L Canister plastic | • 60 L Drum sheet metal |
| • 6 L Canister plastic | • 200 L Drum sheet metal |
| • 7 L Canister plastic | • 1000 L Container |

Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.

Notes

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.