

Sinova Marine TPEO 30 BN 30

Trunk piston engine oil

Product description:

Sinova Marine TPEO 30 BN 30 is a high-quality detergent lubricant designed for medium-speed 4-stroke diesel engines operating on distillate fuel, serving as the primary propulsion, auxiliary power, and for power generation purposes. It complies with API CF performance requirements.

Application:

Sinova Marine TPEO 30 BN 30 is recommended for medium-speed engines in marine, power generation, and industrial applications that run on distillate fuel with API CF diesel detergency specifications. It is also well-suited for various components such as plain bearings of turbochargers, most reduction gears, shaft bearings, stern tubes, and seals.

Features & Benefits:

- Strong detergency and dispersancy
- Improved demulsibility
- Enhanced thermo-oxidative stability
- Reliable rust and corrosion protection
- Exceptional deposit control
- Extended oil life

Typical Properties

Property	Unit	Test method	Typical value
Kinematic Viscosity at 100°C	cst	ASTM D 445	11.30
Kinematic Viscosity at 40°C	cst	ASTM D 445	101.2
Viscosity Index	-	ASTM D 2270	98
Flash Point, COC	°C	ASTM D 92	246
Pour Point	°C	ASTM D 7346	-21
TBN	mg KOH/g	ASTM D 2896	30.0
Sulphated Ash content	%	ASTM D4294	3.9
Density at 15°C	g/ml	ASTM D 4052	0.905

Typical property characteristics are based on current production. Whilst future production will conform to Sinova specifications, variations in these characteristics may occur.

Performance claims

- MAN ES
- Wärtsilä

Sinova Marine TPEO 30 BN 30

Trunk piston engine oil**Health, Safety & Environment:****Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website:

www.sinovagroup.ch

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Available pack sizes:

- 200 L Drum sheet metal
- 1000 L Container

Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.

Notes

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.

© 2016-2025 | All rights reserved

The logos and trademarks used herein are properties owned by Sinova Group AG.