



Aminol TEp-15

Product Data Sheet

Transmission oil

Product description

Aminol TEp-15 is a multigrade gear oil manufactured from a mineral base oil, enhanced with a high-quality additive package to improve anti-wear and low-temperature properties. It is specifically designed for equipment operating in temperate climates.

Application

Aminol TEp-15 is suitable for spur, bevel, and spiral bevel gears of tractors and other farm machinery, as well as for other vehicles and equipment where API GL-2 oils are required. It is recommended for regions with a temperate climate.

Features & Benefits

- Excellent extreme pressure and anti-oxidation properties
- Provides needed wear protection for gears and bearings under moderate conditions
- Extends transmission component life, reducing maintenance costs
- Compatible with common sealing materials

Typical Properties

Property	Unit	Test method	Typical value
Density at 15°C	g/cm ³	GOST 3900	0.890
Kinematic Viscosity at 100°C	mm ² /s	GOST 33	15.20
Kinematic Viscosity at 40°C	mm ² /s	GOST 33	162.4
Viscosity Index	-	GOST 25371	94
Flash Point (COC)	°C	GOST 4333	248
Pour Point	°C	GOST 20287	-21

Typical property characteristics are based on current production. Whilst future production will conform to Aminol specifications, variations in these characteristics may occur.

Performance claims

- API GL-2
- SAE 90
- GOST 23652-79



Aminol TEp-15

Product Data Sheet

Transmission oil

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained. For further guidance on Product Health & Safety, refer to the appropriate Safety Data Sheet, which can be obtained upon request or through our website: www.aminol.az

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil, or water.

Available pack sizes

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 7 L Canister plastic
- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun, or freezing conditions.

Notes

This data sheet and the information it contains are believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application, and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services, and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.

© 2016-2025 | All rights reserved

The logos and trademarks used herein are properties owned by ALCO LLC.



ALCO LLC

3, Vali Mammadov st., Sabail dist., Baku, Azerbaijan, AZ1095

✉ info@aminol.az

2/2