

Sinova Marine COMPRESSOR 100

Compressor Oil

Product description:

Sinova Marine COMPRESSOR 100 is a high-performance lube oil specially engineered to meet the stringent requirements of major compressor manufacturers. It has been blended from carefully selected base oils and a well-balanced additive package to ensure excellent corrosion protection and ageing resistance, as well as a low tendency to form carbon residues and deposits.

Application:

- Reciprocating compressors transmitting air, inert (non-corrosive) and hydrocarbon gases
- Reciprocating compressors up to 160 °C compression discharge temperature
- Oil-lubricated sliding and rolling bearings

Features & Benefits

- Remarkable anti-wear performance
- Better low-temperature fluidity
- Resistant to aging over time
- Decreased deposits in discharge lines
- Improved water-separating properties

Typical Properties

Property	Unit	Test method	Typical value
ISO viscosity grade	-	-	100
Density at 15°C	g/cm ³	ASTM D 4052	0.888
Kinematic Viscosity at 40°C	mm ² /s	ASTM D 445	100.0
Kinematic Viscosity at 100°C	mm ² /s	ASTM D 445	10.93
Viscosity Index	-	ASTM D 2270	92
Flash Point, COC	°C	ASTM D 92	234
Pour Point	°C	ASTM D 7346	-18

Typical property characteristics are based on current production. Whilst future production will conform to Sinova specifications, variations in these characteristics may occur.

Performance claims

- DIN 51506 VB and VC
- ISO 3448 VG 100
- ISO 6743/3A (L-DAA)

Sinova Marine COMPRESSOR 100

Compressor Oil

Health, Safety & Environment:

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website:

www.sinovagroup.ch

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Available pack sizes:

- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.

Notes

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.