

# Sinova Marine Grease BIO EP2

## Grease

### Product description:

Sinova Marine Grease BIO EP2 is an environmentally acceptable lubricating grease. It is thickened using a lithium/calcium compound and is made from fully saturated renewable esters.

### Application:

This product is ideal for use in sensitive marine environments and is suitable for a wide range of marine applications that require NLGI 2 grease.

- Rudder stocks
- Propeller hubs and caps
- Wire ropes
- Winches
- Deck equipment
- General greasing points

### Features & Benefits:

- Offers good resistance to the washing action of rain and seawater.
- Effective corrosion protection for metals commonly found in the marine environment.
- Resistant to oxidation.
- Compatible with nitrile and fluoroelastomers.

### Typical Properties

Property	Unit	Test method	Typical value
NLGI class	-	-	2
Colour	-	Visual	Amber Grease
Worked penetration	-	IP 50	274
Kinematic viscosity of base oil at 40 °C	cst	IP 71	150
Dropping Point	°C	IP 132	178

Typical property characteristics are based on current production. Whilst future production will conform to Sinova specifications, variations in these characteristics may occur.

# Sinova Marine Grease BIO EP2

**Grease****Health, Safety & Environment:****Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website:

[www.sinovagroup.ch](http://www.sinovagroup.ch)

**Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

**Available pack sizes:**

- metal bucket 18.0 kg
- metal barrel 180.0 kg

**Storage**

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.

**Notes**

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.