



Aminol Antifreeze G12+ Ready Mix -40°C

Product Data Sheet

Antifreeze

Product description

Aminol Antifreeze G12+ Ready Mix -40°C is a ready-to-use automotive radiator fluid comprising demineralized water, ethylene glycol, and a state-of-the-art blend of balanced corrosion inhibitors employing OAT technology. It has been designed to provide outstanding protection against frost, corrosion and, overheating for engines of both ferrous and aluminum construction.

Application

- Prevents deposits effectively
- Provides reliable protection for metals and alloys (brass, copper, alloy-treated steel, cast iron, aluminum) from all forms of corrosion
- Offers unsurpassed protection against cavitation
- Minimizes foam formation
- Enhances heat transfer
- Extends service life in cooling systems

Features & Benefits

- Aminol Antifreeze G12+ Ready Mix -40°C is suitable for all types of radiators made of cast iron, aluminum, copper alloys, or their combinations. It is especially recommended for modern engines, where high-temperature protection of aluminum is particularly important.
- This product is ready to use and does not require dilution with water.

Typical Properties

Property	Unit	Test method	Typical value
Appearance	-	Visual	Clear, green/blue homogenous liquid
Density at 15.5 °C	g/cm ³	ASTM D 4052	1.07
Initial Crystallization Point	°C	ASTM D 1177	-37
Boiling point	°C	ASTM D 1120	120
pH	-	ASTM D 1287	8.2



Aminol Antifreeze G12+ Ready Mix -40°C

Product Data Sheet

Antifreeze

Typical property characteristics are based on current production. Whilst future production will conform to Aminol specifications, variations in these characteristics may occur.

Performance claims

- AFNOR NF R15-601 (France)
- AS 2108 (Australia)
- ASTM D3306 (USA)
- ASTM D4656 (USA)
- ASTM D4985 (USA)
- BS 6580: 2010 (UK)
- CUNA NC 956-16
- FVV Heft R443
- SAE J 1034
- NATO S-759
- UNE 26361-88
- Cummins CES 14603
- DAF 74002
- Ford WSS-M97B44-D
- General Motors GM 6277M
- MAN 324 SNF
- MB 325.3
- Renault 41-01-001
- SEAT TL 774 D & F
- Skoda TL 774 D & F
- Volkswagen VAG TL 774 D & F
- Volvo VCS

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety, refer to the appropriate Safety Data Sheet, which can be obtained upon request or through our website: www.aminol.az

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.



Aminol Antifreeze G12+ Ready Mix -40°C

Product Data Sheet

Antifreeze

Available pack sizes

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 7 L Canister plastic
- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun, or freezing conditions.

Notes

This data sheet and the information it contains are believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application, and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services, and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.