

Sinova Marine Motortech 2T Outboard

Motorcycle Oil

Product description:

Sinova Marine Motortech 2T Outboard is a highly reliable two-cycle engine oil designed for outboard engines. It is formulated with high-quality mineral base stocks, highly effective ashless additives, and a high-flash-point solvent.

Application:

Sinova Marine Motortech 2T Outboard is recommended for use in two-cycle water-cooled outboard engines for boats and personal watercraft (Jet Skis, Wave Runners, etc.), where engine oil meeting the requirements of NMMA TCW3 is required. The product is compatible with all types of gasoline (unleaded and leaded) and does not tend to form gel structures.

Features & Benefits:

- Effortless fuel mixing
- Exceptional wear protection
- Safeguarding against engine and exhaust system deposits
- Consistent ignition system performance
- Minimal smoke emission

Typical Properties

| Property | Unit | Test method | Typical value |
|-------------------------------|------|-------------|---------------|
| Kinematic Viscosity at 100°C | cst | ASTM D 445 | 14.50 |
| Flash Point, COC | °C | ASTM D 92 | 228 |
| Pour Point | °C | ASTM D 7346 | -33 |
| Mechanical impurities content | % | ASTM D 874 | 1.43 |
| Density at 15°C | g/ml | ASTM D 4052 | 0.866 |

Typical property characteristics are based on current production. Whilst future production will conform to Sinova specifications, variations in these characteristics may occur.

Performance claims

- NMMA TC-W3

Sinova Marine Motortech 2T Outboard

Motorcycle Oil**Health, Safety & Environment:****Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

For further guidance on Product Health & Safety refer to the appropriate Safety Data Sheet which can be obtained upon request or through our website:

www.sinovagroup.ch

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Available pack sizes:

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 7 L Canister plastic
- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.

Notes

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.