

# Aminol Hydraulic HVLP 150 Product Data Sheet

Hydraulic oil

# **Product description**

Aminol Hydraulic HVLP 150 is a high-performance anti-wear hydraulic oil derived from premium quality raffinates. Engineered to deliver exceptional protection and performance, it excels in various applications, including most mobile equipment, operating efficiently across a wide range of ambient temperatures.

### **Application**

- Industrial and mobile equipment hydraulic systems operating at high pressures and temperatures in critical applications
- Systems where cold start-up and high operating temperatures are typical
- Systems requiring a high degree of load-carrying capability and anti-wear protection
- Machines employing a wide range of components using various metallurgies

#### **Features & Benefits**

- · Exceptional thermal and oxidation stability
- Superior wear resistance
- · Enhanced corrosion protection
- · Excellent anti-foam properties
- · Ultra clean performance

# **Typical Properties**

Property	Unit	Test method	Typical value
ISO viscosity grade	-	-	150
Density at 15°C	g/cm3	ASTM D4052	0.890
Kinematic Viscosity at 40°C	mm2/s	ASTM D445	150.0
Kinematic Viscosity at 100°C	mm2/s	ASTM D445	14.61
Viscosity Index	-	ASTM D2270	95
Flash Point (COC)	°C	ASTM D92	230
Pour Point	°C	ASTM D97	-15
Water separability	min	ASTM D7451	15
-time to 3 ml emulsion min	min	ASTM D7451	15
Oxidation Stability after			
1000h/TAN increase	min	ASTM D4310	<1.5
Copper Strip Corrosion,			
3 h, 100 °C	-	ASTM D130	11
Rust-Preventing Characteristics,			
A&B	-	ASTM D665	11



# Aminol Hydraulic HVLP 150 Product Data Sheet

Hydraulic oil

FZG EP Wear Test (A 8.3/90)	-	ASTM D 5182	15	
Failure Load Stage	-	ASTM D 5182	15	

Typical property characteristics are based on current production. Whilst future production will conform to Aminol specifications, variations in these characteristics may occur.

#### **Performance claims**

- DIN 51524-3 (HV)
- ISO 11158 (HV)
- ASTM D6158 (HV)
- SAE MS 1004
- AIST 126/127
- GB 11118.1-2011 (L-HV)

# **Health, Safety & Environment**

### **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained. For further guidance on Product Health & Safety, refer to the appropriate Safety Data Sheet, which can be obtained upon request or through our website: www.aminol.az

#### **Protect the Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil, or water.

### Available pack sizes

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 7 L Canister plastic

- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

#### **Storage**

- · We recommend to store all packages under cover.
- Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun, or freezing conditions.



# Aminol Hydraulic HVLP 150 Product Data Sheet

Hydraulic oil

#### **Notes**

This data sheet and the information it contains are believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application, and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services, and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.



The logos and trademarks used herein are properties owned by ALCO LLC.

