



Aminol Transmission 140 GL-1

Product Data Sheet

Transmission oil

Product description

Aminol Transmission 140 GL-1 is a mineral-based gear oil with rust and oxidation-inhibiting properties. Manufactured from highly refined base stocks and chosen performance additives, it has been tailored for application in automotive and industrial gearboxes, as well as manual transmissions, where API GL-1 straight mineral, non-EP lubricant in SAE viscosity grades 140 is recommended.

Application

Aminol Transmission 140 GL-1 is recommended for many types of automotive and industrial equipment where the equipment suppliers recommend the use of a straight mineral oil in SAE viscosity grades 140.

Features & Benefits

- Optimal lubricant film formation via high-viscosity index base stocks
- Enhanced rust protection for prolonged equipment life
- Efficient antifoam properties for extended gear and bearing longevity

Typical Properties

Property	Unit	Test method	Typical value
Density at 15°C	g/cm ³	ASTM D 4052	0.896
Kinematic Viscosity at 100°C	mm ² /s	ASTM D 445	25.20
Kinematic Viscosity at 40°C	mm ² /s	ASTM D 445	348
Viscosity Index	-	ASTM D 2270	95
Flash Point, COC	°C	ASTM D 92	260
Pour Point	°C	ASTM D 7346	-12

Typical property characteristics are based on current production. Whilst future production will conform to Aminol specifications, variations in these characteristics may occur.

Performance claims

- API GL-1

Health, Safety & Environment

Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.



Aminol Transmission 140 GL-1

Product Data Sheet

Transmission oil

For further guidance on Product Health & Safety, refer to the appropriate Safety Data Sheet, which can be obtained upon request or through our website: www.aminol.az

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil, or water.

Available pack sizes

- 1 L Canister plastic
- 4 L Canister plastic
- 5 L Canister plastic
- 6 L Canister plastic
- 20 L Canister plastic
- 30 L Canister plastic
- 200 L Drum sheet metal
- 1000 L Container

Storage

- We recommend to store all packages under cover.
- Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings.
- Products should not be stored above 60 °C, exposed to hot sun, or freezing conditions.

Notes

This data sheet and the information it contains are believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application, and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by ALCO LLC for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services, and information supplied are provided under our standard conditions of sale. You should consult our sales specialists if you require any further information.